



FITTING THE COUNTRY 4 MKII OPTIONAL RIDDLING GRATE

TOOLS REQUIRED:

- 10mm Spanner
- Phillips screwdriver

1. Before fitting the riddling grate remove the coal retainer and wood ash retainer. The wood ash retainer is not required when the riddling grate is fitted.
2. Undo the nut on the riddling blanking hole using a 10mm spanner. Remove the cover and spacing washer (ensure you keep these in a safe place as you will need to replace them if the coal grate is removed).
3. Feed the riddler rod through the hole on the right hand side of the stove, and slide one washer onto the rod. If there is not sufficient room to the right of the stove to do this, remove the riddler rod, fit one washer over the rod then slide the rod through the hole from the inside of the stove.
4. Feed the rod through the two side fireplates and slide the other washer on to the rod so that the washers end up outside the two side fireplates. With the side fireplates pushed together fit the retaining clips so that the washers come inside the clips.
5. Slide the fireplates apart so that they rest against the sides of the firebox. Slot in the front and rear support plates.
6. Fit the riddling plates into position through the rear and front grate support plates, making sure they locate correctly onto the riddling rod.
7. Re-fit the coal retainer supplied with the stove (not included with this kit), the wood ash retainer (also supplied with the stove) is not required when the multifuel kit is fitted.
8. Slide the ashpan under the grate.

