

UK - DIRECTION OF USE:

Please read all instructions and warnings before using "Morsø Gas Lighter".

- To fill gas tank. Turn unit upside down and firmly push the butane can into the filling valve. The tank should be filled in 10 seconds. Please allow a few minutes after filling for the gas to stabilize.
- To ignite the "Morsø Gas Lighter". Firstly, turn the gas adjustment knob in counter-clockwise. Secondly, press the automatic safety lock. Then press the ignition button.
- Lose the flame burning. Just press the continuous flame button when the flame is burning.
- j. To shut off "Morsø Gas Lighter". Press the ignition button and the flame will extinguish. Then turn the gas flow control knob in clockwise direction when not in use.
- Adjustment of flame: you may increase gas flow and flame length by turning the gas flow control knob in counter-clockwise direction.

Approximate operating time per filling - over 45 minutes.

CARE AND USE INSTRUCTIONS: Warning:

READ ALL CARE AND USE INSTURCTIONS thoroughly before using "Morsø Gas Lighter" and retain for future use.

To clean, ensure "Morsø Gas Lighter" is in the flame lock "off" position and cool to touch, wipe main body and stand with damp cloth and dry immediately.

CAUTION: EXTREMELY HOT FLAME

- Accessible parts may become very hot. Keep young children away from the the gas lighter.
- Butane gas is extremely flammable, please handle with care.
- Always point away from face and body when igniting or operating "Morsø Gas Lighter". The flame may be difficult to see, so work with care.
- DO NOT touch flame guard/nozzle during or after using with hands or any other combustible materials, until nozzle has cooled.
- DO NOT use "Morsø Gas Lighter" continually for longer than 10 minutes.
- 6. Do not leave lit the gas lighter unattended.
- Make sure the that the "adjustment knob" is firmly closed and the flame is completely extinguished after use.
- 8. DO allow the gas lighter to cool before storing.
- DO NOT store under direct sunlight or in any area where temperature exceeds 40C

- 10. The gas lighter may not ignite if temperature is too cold or insufficient oxygen is available.
- 11. Never puncture or put in fire. Do not disassemble the gas lighter.
- 12. Do not use the the gas lighter if it has damaged or worn seals
- Do not use a gas lighter which is leaking, damaged or which does not operate properly.
- 14. If there is a leak on your gas lighter (smell of gas), take it outside immediately into a well ventilated flame free location where the leak may be detected and stopped. If you wish to check for leaks on your the gas lighter, do it outside. Do not try to detect leaks using a flame, use soapy water.
- 15. Do not modify the "Morsø Gas Lighter".

Made in China